

TRADE COMBINE

20, Industrial House, 51/53, Nagdevi Cross Lane, Mumbai: 400 003. INDIA.

Tel: + 91 - 22 - 2345 3999 / 2346 5999. Fax: + 91 - 22 - 2344 0101.

E-mail: tradecombine@vsnl.net Website: www.tradecombine.com

N A G

BORE / CRANKSHAFT / GRINDING GAUGES

NAG bore gauges are manufactured in split collet and centering bridge type with interchangeable fixed anvil types.

SPLIT COLLECT TYPE

Bore gauges up to 18 mm dia incorporate interchangeable, hard chromed, spring loaded, self centring split measuring heads. A precision lapped conical expander pin inside transfers the measuring movement of the split head directly to the indicator.

INTERCHANGEABLE FIX ANVIL TYPE

The movable, hardened measuring anvil (front plunger) located diametrically opposite the interchangeable fixed anvil, transfers its movement to the indicator thru a lever stroke push rod system. A centering bridge ensures positioning of the two measuring points at the extremities of true diameter, Properly selected fixed anvil and spacer gives the desired dimensions to be measured.

ADVANTAGES	MODEL	RANGE	TYPE	BORE	ANVILS	SPACER	EX T.P.C.	PRICE
a) Spares like anvils, clamps Ex-stock.		IN MM		DEPTH				
b) All ranges off the self.	SBG1S	10-Jun	Collet	40	8			3510
	SBG1SE	10-Jul		40	6			2919
c) Stainless steel rod, totally rust free.	SBG2	18-Oct		60	8			2847
d) Chinese type models also available.	BG1	18-35	Anvil	170	9	2		1950
	BG1.1	22-50		170	7	2	1	2106
	BG2	35-60		200	6	4		2106
e) Extra long depth available on demand.	BG3	50-100		250	11	4		2418
	BG3E	50-150		250	11	4	1	2535
f) Equivalent inch or special bore	BG3.1	110-160		250	13	4	1	3510
	BG4	150-250		350	11	4	1	4173
gauges manufactured.	BG5	250-400	Teles copic	450	1	1	1	7020

Prices are without dial gauges

CRANKSHAFT DEFLECTION GAUGE

For checking bearing alignment or shaft deflection in Diesel Engines.

IN PROCESS GRINDING GAUGE

For use on cylindrical grinding machines for diameter gauging during the grinding process.

- ☛ Maximum Accuracy
- ☛ Transfer of Motion.
- ☛ Universal Application
- ☛ Constant Measuring Pressure.

CAT NO.	RANGE	DIAL L.C.	PRICE
CDG1	60-450 MM	0.01 MM	11070
CDG 2	60-250 MM	0.01 MM	10350

CAT NO.	RANGE	DIAL L.C.	PRICE
G G 1	10-75 MM	0.01 MM	26910
G G 2	75-150 MM	0.01 MM	28260
G G 3	150-225 MM	0.01 MM	30600
G G 4	225-300 MM	0.01 MM	35910

P & F / Taxes extra as applicable . Prices and Technical Specifications subject to change without notice.